



PRODUCT CODE: HD-430 PRINZOL HDD 15W-40 CJ-4

PRINZOL 15W-40 Super Duty is designed for diesel engine vehicles and provides excellent lubricant properties to ensure a long lasting engine life cycle.

Prinzol 15W-40 Super Duty engine oil is a blended from high quality Group II base stocks with state of the art premium additive technology to provide extended engine life technology, and is formulated to provide the highest levels of equipment protection available.

PRINZOL 15W-40 Super Duty Synthetic Blend is recommended for heavy duty diesel engines that require API CI-4, Detroit Engine Oil 93K218, Cummins CES 20081, Caterpillar ECF-3, Mack EO-O Premium Plus and, Volvo VDS-4.

PRINZOL 15W-40 Super Duty Synthetic Blend provides a combination of synthetic and conventional oil for top class HD oil for use in diesel powered vehicles or other equipment which is powered by either gasoline or diesel. Our Semi-Synthetic 15W-40 can be recommended diesel engines powered with Exhaust Gas Recirculation (EGR) technology and other vehicles EPA 07 compliant motors of both older and newer vehicles

Recommended For

PRINZOL 15W-40 Super Duty CJ-4 is formulated for applications including:

- When CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF-4 CF, CF-2 oils are required.
- When SM, SL, SJ, SH, SG, SF oils are required.
- When a US Military CID A-A-52306 performance level is required.
- When MIL-L-210E/F oils performance level is required.
- ACEA E7, E5-02, JASO DHD-1, Global DHD-1
- When GM4718M/6094M and Ford M2C153-E oils are required.
- In all diesel and gasoline engines, including turbo-charged models.
- Detroit Engine Oil, DDC 93K218
- In Caterpillar engines ECF-3
- Mack Engines EO-O, EO-N, EO-M, Premium Plus, EO-M, EO-L Plus, EO-L, EO-K/2
- In Cummins engines CES 20071, 20076, 20077, 20078, 20081
- In Volvo VDS-4, VDS-3, VDS-2, and VDS engines

PRINZOL LUBRICANTS, INC



Product Data Sheet Rev 03/08/2016

- Caterpillar Engines ECF-1-a & Drive Trains TO-2
- When Allison C-3/C-4 fluids are required
- Mercedes Benz MB 228.3

Specifications

The table below indicates the physical and chemical properties of Prinzol 15W-40 Super Duty CJ-4 motor oil.

- Follow equipment manufacturer recommendations for specific applications.

| | |
|------------------------|---|
| SAE GRADE: | 15w-40 |
| Product Code | HD-430 |
| Gravity, API | 30.0 |
| Pour Point: °C | -32 |
| Flash Point: °C | 231 |
| Viscosity @40°C, cSt | 111 |
| Viscosity @ 100°C, cSt | 15.5 |
| Viscosity Index | 146 |
| Borderline Pumping: °C | 20 |
| Sulfated Ash wt% | >1.0 |
| Total Base Number | 10 |
| API Licensed Service: | CJ-4, CI-4 PLUS, CI-4, CH-4, CF-4, CF, CF-2, CE, CD-II/SL, SM |