

Prinzol Red Ex-Life 50/50.

A promotional graphic for Prinzol Red Ex-Life 50/50. On the left is the Prinzol logo with a red star and the text "PRINZOL™ RED EX-LIFE". In the center, white text describes the product as an extended life anti-freeze/coolant pre-mix for car and truck engines, providing a service life of 5 years or 150,000 miles. Below this, the text "- Red Ex-Life 50/50" is written in large, bold, red letters. On the right is a black plastic jug of the product. At the bottom, a red banner contains the text "OAT (organic acid technology)" in white.

Prinzol-Red Ex-Life 50/50 is an extended life anti-freeze/coolant pre-mix for car and truck engines. It will provide a service life of 5 years or 150,000 miles and is suitable for use in foreign and domestic passenger cars, vans, SUVs and light trucks requiring extended life antifreeze.

Prinzol –Red Ex-Life 50/50 is formulated with an all-organic OAT (organic acid technology) inhibitor package. It contains no phosphate, silicate, amines, borate or nitrite.

Prinzol-Red Ex-Life 50/50 contains ingredients to provide broad-range metal protection and guard the cooling system against corrosion and cavitation-erosion. In addition, it contains additives to minimize hot surface scaling while also preventing heat transfer surface fouling due to minor oil leakage.

Prinzol-Red Ex-Life 50/50 is a ready to use, premix (50/50) product. DO NOT DILUTE with water. It can provide freeze



protection to -34°F and boil over protection up to $+265^{\circ}\text{F}$ (w/15psi). It is fully compatible with all major brands of premium, antifreeze/ coolants. It DOES NOT contain any recycled antifreeze.

Prinzol-Red Ex-Life 50/50 can be mixed with most major brands of straight-OAT and conventional Antifreezes without the precipitation problems encountered with non-hybrid products.

Prinzol-Red Ex-Life 50/50 requires an SCA for HD diesel truck service. Prinzol-Red Ex-Life 50/50 is an extended life formula.

Prinzol-Red Ex-Life 50/50 protects all cooling system components with multi metal corrosion inhibitors, and has lubricating properties.

Specifications

- EG CONTENT 47-48%
- INHIBITORS >1%
- COLOR: Red
- SPEC GRAVITY 1.06
- pH(as is) 8.5-9.5
- FREEZE PT(as is) -34°F
- BOIL PT(as is) $+265^{\circ}\text{F}$
- Meets: ASTM D3306 D4985 D1384, D4340, D2570, D2809

Cooling System Recommendations

A clean cooling system is required for the protection of your vehicle/ equipment. When changing coolant, always drain and flush your system thoroughly before refilling with recommended coolant. Maintain coolant levels properly. Always top-off with premix coolant. Change coolant regularly to remove contamination that may develop from engine gases or other fluids. Always follow manufacturers' service recommendation.

call us for MSDS (315)363-3898