

# PRINZOL LUBRICANTS, INC



Product Data Sheet Rev 03/08/2016

## UNIVERSAL TRACTOR HYDRAULIC FLUID (303) CODE: HY-450

PRINZOL Universal Tractor Hydraulic Oil Fluid 303 (UTHF 303) is a general purpose tractor hydraulic fluid is made for long term service and for Severe weather conditions.

It is a premium Grade tractor hydraulic fluid with highly refined base stocks which provides water sensitivity, anti-wear, PTO clutch, rust protection; extreme pressure properties, , foam suppression and brake chatter reduction.

Suggested usable temperature range is ambient temperatures between +32°F and 104°F.

PRINZOL's UTHF 303 may be recommended for: Deutz®, Ford®, Allis Chalmers®, Allison®, Caterpillar®, Tractor, International Harvester®, JI Case®/David Brown®, John Deere® 303, J20A, Kubota®, Massey Ferguson®, Oliver®, and White® tractors.

Note: Please check the Equipment manufacturer Guide and owner's manual for recommendations of a lubricant selection and to determine the suitability of a oil or Lubricants for a specific application.

### Specifications

Product Code	HY-450
SAE Grade	20
Viscosity @ 40°C cSt	56.02
Viscosity @ 100°C cSt	9.63
Viscosity Index	148
Flash Point: COC, °C	204
Pour Point: °C	-17
API Gravity	30.2

**\*Follow equipment manufacturer recommendations for specific applications.**