



PRODUCT CODE: HD-410 PRINZOL Full Synthetic 15W-40 CJ-4

PRINZOL 15W-40 Full Synthetic Motor Oils are designed for use in turbocharged, supercharged and high rpm engines of diesel cars and diesel light duty trucks which experience increased heat. PRINZOL Full Synthetic Oils are compatible with domestic and foreign gasoline engine vehicles.

Prinzol Full Synthetic 15W-40 is one-hundred percent full synthetic, multi-grade motor oil blended from high quality base oils with state of the art premium additive technology to provide extended engine life, and are formulated to provide the highest levels of equipment protection available. PRINZOL Full Synthetic 15W-40 provides enhanced high temperature deposit control, minimized oil consumption and increased fuel economy and protects the engine against rust and corrosion.

Prinzol Full Synthetic Oils are specifically blended for vehicles functioning under extreme conditions where supreme protection is required.

Benefits and Features

PRINZOL Full Synthetic Motor Oils are designed for excellent fuel economy, minimized oil consumption and excellent protection from deposits at all operating temperatures.

PRINZOL Full Synthetic Motor Oils are designed to deliver engine protection from bearing corrosion and delivers anti-wear, anti-foam and anti-rust properties, and good cold-cranking capabilities. Our Synthetic Oils helps to prevent thermal breakdown.

Recommended For

PRINZOL Full Synthetic Motor Oils are formulated for applications including:

- When CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF, CF-2 oils are required.
- When SM, SL, SJ, SH, SG, SF, oils are required.
- In all diesel and gasoline engines, including turbo-charged models.
- Detroit Diesel Oil, DDC 93K218
- Cummins Engines CES 20071,20077, 20076, 20078, 20081,
- Allison C-3/C-4
- When U.S. Military CID A-A-52306 are required.
- When MIL-L-210E/F oils performance level is required.
- When GM 4718M/6094M and Ford M2C 1 53-E are required.



- Caterpillar ECF-1a & Drive Trains TO-2
- Mercedes Benz MB 228.3
- Renault, RLD-3
- In Caterpillar engines ECF-3
- Mack engines (EO-O, EO-N, EO-M, EO-M Plus, EO-L Plus, EO-L)

Specifications

The table below indicates the physical and chemical properties of Prinzol Full Synthetic 15W-40 Motor oil.

- Follow equipment manufacturer recommendations for specific applications.

SAE GRADE:	HD 15w-40
Product Code	HD-410
Gravity, API	31.5
Pour Point: °C	-37
Flash Point: °C	249
Viscosity @40°C, cSt	111
Viscosity @ 100°C, cSt	15.5
Viscosity Index	146