



EHD 15W-40CF CODE HD-410

PRINZOL 15W-40 Super Duty is designed for diesel engine vehicles and provides excellent lubricant properties to ensure a long lasting engine life cycle.

Prinzol 15W-40 Super Duty engine oil is a blended from high quality base stocks with state of the art premium additive technology to provide extended engine life. Prinzol 15W-40 helps to prevent oil thickening and protects against rust, corrosion, oxidation and high temperature deposits.

Our 15W-40 is specifically designed to control soot buildups and delivers excellent engine performance.

Recommended For:

- CI-4, CH-4, CG-4, CF-4, CF, CF-2, CE and CD-II
- SL, SJ, SH, SG, SF. SE. SD or SC
- U.S. Military CID A-A-52306
- MIL-Prf-2104/G or the former MIL-L-46152D
- GM 4718M/6094M
- Detroit Diesel 7SE 270, SERIES 51, 71, 92 and TSB 01-TS-07 engines
- Mack engines (EO-N, EO-M, EO-L Plus, EO-L, EO-K/2)
- Cummins engines CES 20071, 20076, 20078
- Caterpillar drive trains (TO-2), Allison C-3/C-4
- Fuller, Eaton, and Spicer transmissions
- Caterpillar ECF-1

TYPICAL TEST DATA:

Follow equipment manufacturer recommendations and conventional guides to determine the best oil for specific applications.

| | |
|------------------------|----------------------|
| SAE GRADE: | EHD 15W-40 CF |
| Product Code | HD-410 |
| Gravity, API | 29.0 |
| Pour Point: °C | -30 |
| Flash Point: °C | >260 |
| Sulfated Ash % Weight | 1.2 |
| Viscosity @ 100°C, cSt | 15.5 |
| Viscosity Index | 135 |

**Follow equipment manufacturer recommendations for specific applications.*